

## Features

- Radial leaded devices
- Very high voltage surge capabilities
- Lead-free and compliant with the European Union RoHS Directive 2002/95/EC
- Agency Recognition: UL、CSA、TUV



## Applications

- Customer Premise Equipment
- MDF modules
- Network Interface Devices
- Base station
- Power supply

## Product Dimensions

Part number	A	B	C	D	E	Lead
	Max	Max	Max	Min	Typ	Size(φ)
LBV150	13.5	12.6	6.5	4.7	5.1	0.6
LBV160	13.5	12.6	6.5	4.7	5.1	0.6





Figure 2

### Marking system



\*The suffix "U" means no outside envelop

\* Lead materials: Tin-plate metal wire.

## Electrical Characteristics

Part number	$I_H$	$I_T$	$T_{trip}$	$V_{max\ interrupt}$	$I_{max}$	$Pd_{typ}$	$R_{min}$	$R_{max}$
	(A)	(A)	Current(A) Time(S)	(V)	(A)	(w)	(Ω)	(Ω)
LBV150	0.150	0.300	1.00 5.00	600	3.0	1.0	6.00	12.00
LBV160	0.160	0.320	1.00 7.00	600	3.0	1.0	4.00	10.00

$I_H$ =Hold current: maximum current at which the device will not trip at 25°C still air.

$I_T$ =Trip current: minimum current at which the device will always trip at 25°C still air.

$V_{max\ interrupt}$ =Maximum interrupt voltage device can withstand without damage at rated current.

$I_{max}$ =Maximum fault current device can withstand without damage at rated voltage.

$T_{trip}$ =Maximum time to trip at assigned current.

$Pd_{typ}$ =Typical power dissipation: typical amount of power dissipated by the device when in state air environment.

$R_{min}$ =Minimum device resistance at 25°C prior to tripping.

$R_{max}$ =Maximum device resistance at 25°C prior to tripping.

## Thermal Derating Chart-Ih(A)

Part number	Maximum ambient operating temperatures(°C)								
	-40	-20	0	25	40	50	60	70	85
LBV150	0.238	0.211	0.183	0.150	0.128	0.115	0.101	0.088	0.067
LBV160	0.250	0.220	0.195	0.160	0.147	0.123	0.110	0.095	0.074


## Test Procedures And Requirements

Test	Test Conditions	Accept/Reject Criteria
Resistance	In still air @ 25°C	$R_{min} \leq R \leq R_{max}$
Time to Trip	Specified current, $V_{max}$ , 25°C	$T \leq$ maximum Time to Trip
Hold Current	30min, at $I_H$	No trip
Trip Cycle Life	$V_{max}$ , $I_{max}$ , 100cycles	No arcing or burning
Trip Endurance	$V_{max}$ , 24hours	No arcing or burning

## Typical Time-to-trip Charts at 25°C

A=LBV160

B=LBV150



## Package Information

Bulk:

LBV150~LBV160.....1000pcs per bag

Tape & Reel:

LBV150~LBV160.....600pcs per reel

### Notices:

The devices are intended for protection against occasional overcurrent or overtemperature fault conditions and should not be used when repeated fault conditions are anticipated.

Operation beyond maximum ratings or improper use may result in device damage and possible electrical arcing and flame.

Shanghai Wayon Thermo/Electro Materials Co.,Ltd.

16th Floor, No.1398, Jinqiao Road, Shanghai 200136,China

Tel: 86-21- 50310888

E-mail: market@way-on.com

Fax: 86-21-50757680

Http://www.way-on.com